

Cisco RVS4000 4-port Gigabit Security Router: VPN Cisco Small Business Routers

Highlights

- Secure, high-speed network access for small businesses
- · Gigabit Ethernet connections enable rapid transfer of large files
- · Advanced security, including intrusion prevention, helps keep assets safe
- · Full IPsec VPN capabilities for up to five remote connections

Product Overview

The Linksys® by Cisco® RVS4000 Gigabit Security Router delivers affordable, highly secure network access and switching capabilities at broadband speed to help enable employees of small businesses like yours safely connect to the resources they need to be productive (Figure 1). Strong security features include a proven firewall with intrusion prevention, virtual private network (VPN) capabilities, and an optional service that scans your email and helps fight spam, viruses, and other threats. An integrated 4-port Gigabit Ethernet switch allows up to four devices to share high-speed connectivity in the office.

Figure 1. Linksys by Cisco RVS4000 Gigabit Security Router



Features and Benefits

The Linksys by Cisco RVS4000 Gigabit Security Router offers:

- High-speed connectivity: Gigabit Ethernet connections on both WAN and LAN ports help
 you take full advantage of your broadband connections, enabling your employees to send
 and receive large files quickly and easily.
- Proven Stateful Packet Inspection (SPI) firewall with Intrusion Prevention System
 (IPS): Unlike standard firewalls, which block incoming streams based only on the source or
 type of data, the intrusion prevention system scans deep, enabling it to detect and block
 most worms, Trojan horses, and denial-of-service attacks to help keep your business
 assets safe.
- VPN capabilities: IP Security (IPsec) VPN capabilities built into the RVS4000 enable your remote employees, whether working from home or on the road, to connect to your office network using nearly any VPN client to access files and transfer data as securely as if they were in the office.

- Optional Trend Micro ProtectLink Gateway Security Service: This optional hosted service adds another layer of protection to your network by scanning email and websites to help fight spam, virus, web threats, and data leakage, without the drain on your office PCs caused by traditional security solutions.
- Improved traffic flow and network management: Flexible, built-in support for up to four 802.1Q virtual LAN (VLAN) connections enable separation of network traffic to help improve traffic flow and overall network management while enabling the RVS4000 to interoperate with other VLAN-capable switches (Figure 2).

Figure 2. Linksys by Cisco RVS4000 Gigabit Security Router Port Connections



Product Specifications

Table 1 lists the basic product specifications for the RVS4000 Gigabit Security Router.

Table 1. Product Specifications

Feature	Description
Routing	Static routing Routing Information Protocol (RIPv1 and RIPv2) Inter-VLAN routing
Layer 2	 Port-based and 802.1Q tag-based VLANs 4 active VLANs (4094 range) One of five WAN/LAN ports can be mirrored to a selected LAN port Supports Rapid Spanning Tree Protocol (RSTP) for loop detection and faster reconfiguration
Network	 Dynamic Host Configuration Protocol (DHCP) Server, DHCP Client, DHCP Relay Agent DHCP Server supports static IP address based on MAC address Domain Name System (DNS) Relay, Dynamic DNS (DynDNS, TZO) Network Address Translation (NAT): Port Address Translation (PAT), Network Address Port Translation (NAPT), Session Initial Protocol (SIP) Application Layer Gateway (ALG) support, NAT traversal Network edge software configurable on any IP address
IPv6	 Dual-stack IPv4 and IPv6 6 to 4 Stateless address auto-configuration DHCP v6 Intra Module Command Protocol (IMCP) v6

Security	Access Control
	MAC-based, IP-based access control list (ACL)
	Firewall
	SPI firewall
	Content Filtering
	Static URL blocking or keyword blocking (included)
	Dynamic filtering through Trend Micro ProtectLink Gateway Security Service (optional)
	Intrusion Prevention System (IPS)
	IP sweep detection
	Application anomaly detection (HTTP, FTP, Telnet, Remote Copy Protocol [RCP])
	Peer-to-peer control
	Instant messenger control
	 Layer 3/Layer 4 protocol (IP, TCP, User Datagram Protocol [UDP], Internet Control Message Protocol [ICMP]) normalization
	Secure Management
	• HTTPS
	Username/password
	802.1X
	 Port-based RADIUS authentication (Extensible Authentication Protocol multicast distributed switching [EAP-MDS], Protected Extensible Authentication Protocol [PEAP])
VPN	5 VPN tunnels for remote client access
	5 IPsec gateway-to-gateway tunnels for branch office connectivity
	Triple Data Encryption Standard (3DES) encryption
	 Message Digest Algorithm 5 (MD5)/Secure Hash Algorithm (SHA1) authentication
	• IPsec NAT=T
	 VPN pass-through of Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP), IPsec
Quality of Service	Service-based bandwidth management supports rate control and priority
	Port-based prioritization on LAN port; application-based on WAN port
	• 4 queues
Management	Simple Network Management Protocol (SNMP) version 1, 2c
	Event logging: local, syslog, email alerts
	Firmware upgradable through web browser
	Flash, RAM diagnostics
	Built-in web user interface for browser-based configuration
	T
Performance	NAT throughput: 800 Mbps when IPS is disabled

This Cisco Small Business product comes with 3-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to http://www.cisco.com/go/smallbiz.

System Specifications

Table 2 lists the system specifications of the RVS4000 Gigabit Security Router.

Table 2. System Specifications

Feature	Description
WAN	Gigabit Ethernet (10/100/1000) WAN port
LAN	4-port, full-duplex 10/100/1000 Ethernet switch
Physical dimensions and weight	 W x D x H = 6.69 in. x 1.61 in. x 6.69 in. (170 mm x 41 mm x 170 mm) Weight: 0.84 lb (0.38 kg)
Power	12V 1A

Approvals and compliance	 IEEE 802.3/802.3u IEEE 802.1X (security authorization) RFC 791 (IPv4) RFC 2460 (IPv6) RFC 1058 (RIPv1) RFC 1723 (RIPv2)
Certification	FCC Class B CE ICES-003
Environmental operating range	Operating temperature: 0° to 40°C (32° to 104° F) Storage temperature: -20° to 70°C (-4° to 158°F) Operating humidity: 10 to 85% relative humidity (noncondensing) Storage humidity: 5 to 90% relative humidity (noncondensing)

Configuration Requirements

Table 3 lists the minimum requirements that must be in place in order to install or use the product.

 Table 3.
 System Requirements

Feature	Description
Network adapter	Network adapter with Ethernet network cable installed per PC
Web-based configuration	Java/cookies/SSL-enabled web browser

Ordering Information

Table 4 lists ordering information for the Linksys by Cisco RVS4000 Gigabit Security Router and optional Trend Micro ProtectLink Gateway Security Service.

 Table 4.
 Ordering Information

Part Number	Product Name	
RVS4000	Linksys by Cisco RVS4000 Gigabit Security Router (USA)	
RVS4000-AU	Linksys by Cisco RVS4000 Gigabit Security Router (Australia/New Zealand)	
RVS4000-EU	Linksys by Cisco RVS4000 Gigabit Security Router (Europe)	
RVS4000-UK	Linksys by Cisco RVS4000 Gigabit Security Router (United Kingdom)	
RVS4000-AS	Linksys by Cisco RVS4000 Gigabit Security Router (Asia Pacific)	
RVS4000-SG	Linksys by Cisco RVS4000 Gigabit Security Router (Singapore)	
RVS4000-LA	Linksys by Cisco RVS4000 Gigabit Security Router (Latin America)	
Security Service		
LBATMPG05	1-year subscription to Trend Micro ProtectLink Gateway Security Service	



Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco Stadium Vision, Cisco Tele Presence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncoS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)

Printed in USA C78-496735-00 11/08